


Im Hofstätt 11 D-72359 Dotternhausen Phone +49 (0)7427 9480-0 Fax +49 (0)7427 9480-7025 e-mail info@proactiv-gmbh.de www.proactiv-gmbh.com

 $\epsilon$ 

		SPEEDY 4teen	
☐ Quotation date:_		Active easy runn	ing rigid frame
Consultation was carri	ed out by	wheelchair	
Staff at the medical sup		Maximum user weight	limit 100 kg
PRO ACTIV field repres	sentative:		· ·
		A9050100000 € 3,700	0.00
☐ Order date:			
according to GTC PRO ACTIV	GmbH	t	
		Invoicing address: □	same as company address
Madical aumpliara/aa	mnany addraga.		other (see below)
Medical suppliers/co	mpany address:	Cust. no.: Name:	
Name:		Name. Street:	
Street:		Postcode / city:	
Postcode / city:		Phone:	
Phone:		Fax:	
Fax: E-Mail:		E-Mail:	
Contact:		Contact:	
Shipping address:	same as company address Other (see below)	Body size:	
Name:		J (	
Street:			
Postcode / city:			
Customer name/com Surname,	nmission:	Body height:	cm
forename:		Weight:	kg
Street: Postcode / city: Phone:		<ul><li>Lower leg length:</li><li>(anatomic dimension: hollower</li></ul>	cm ow of the knee to the foot sole):
Fax: E-Mail: D.O.B: Paying			datory for further processing.
organisation:		_	

## Basic size



☐ Size L (Frame length R	39 cm to the bend)
0.10 _ (i	□ 26 □ 27 □ 28 □ 29 □ 30 □ 31 □ 32
Seat width <b>SB</b>	33 34 35 36 37 38
ood main ob	The following dimensions are optionally available $\square_{39}$ $\square_{40}$ $\square_{41}$ $\square_{42}$ $\square_{43}$
Seat depth <b>ST</b>	Subject to surcharge:
•	
Back height <b>RH</b>	30 31 32 33 34 35 36 37 38 39
	□ 20     □ 21     □ 22     □ 23     □ 24     □ 25     □ 26     □ 27     □ 28     □ 29
Lower leg length USL	30 31 32 33 34 35 36 37 38 39
	□ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47 □ 48 □ 49
Seat height back SHh	□ 36 □ 37 □ 38 □ <u>39</u> □ 40 □ 41 □ 42 □ 43 □ 44 for 24" tyres
Seat height front <b>SHv</b>	□ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47
Tipping point <b>KP</b> (Front of back tube up to axis middle drive wheel)	□1 □2 □3 □4 □5 □6 □7 □ <u>8</u> □9 □10
☐ Size XL (Frame length I	R 43 cm to the bend)
	□ 26     □ 27     □ 28     □ 29     □ 30     □ 31     □ 32
Seat width SB	□ 33 □ 34 □ 35 □ 36 □ 37 □ 38
	The following dimensions are optionally available subject to surcharge:
Seat depth <b>ST</b>	□ 36 □ 37 □ 38 □ 39 □ 40 □ 41 □ 42 □ 43
Back height RH	30 31 32 33 34 35 36 37 38 39
	□ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47 □ 48
	□ 20     □ 21     □ 22     □ 23     □ 24     □ 25     □ 26     □ 27     □ 28     □ 29     □ 30
Lower leg length USL	31 32 33 34 35 36 37 38 39 40 41
	□ 42     □ 43     □ 44     □ 45     □ 46     □ 47     □ 48     □ 49     □ 50     □ 51     □ 52
Seat height back SHh	□ 36 □ 37 □ 38 □ 39 □ 40 □ 41 □ 42 □ 43 □ 44 For 24" tyres
Seat height front SHv	40 41 42 43 44 45 46 47
Tipping point <b>KP</b> (Front of back tube up to axis middle drive wheel)	□1 □2 □3 □4 □5 □6 □7 □ <u>8</u> □9 □10
☐ Size XXL (Frame length	R 47 cm to the bend)
	□ 26     □ 27     □ 28     □ 29     □ 30     □ 31     □ 32
Seat width SB	33 34 35 36 37 38
	The following dimensions are optionally available subject to surcharge:
Seat depth <b>ST</b>	□ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47 □ 48 □
•	□ 20     □ 21     □ 22     □ 23     □ 24     □ 25     □ 26     □ 27     □ 28     □ 29
Back height RH	30 31 32 33 34 35 36 37 38 39
	□ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47 □ 48
	□ 20     □ 21     □ 22     □ 23     □ 24     □ 25     □ 26     □ 27     □ 28     □ 29     □ 30
Lower leg length USL	31 32 33 34 35 36 37 38 39 40 41
	□ 42     □ 43     □ 44     □ 45     □ 46     □ 47     □ 48     □ 49     □ 50     □ 51     □ 52
Seat height back SHh	□ 39 □ 40 □ 41 □ 42 □ 43 □ 44 □ 45 □ 46 □ 47 For 24" tyres
Seat height front SHv	□ 43 □ 44 □ 45 □ 46 □ 47 □ 48 □ 49 □ 50
Tipping point <b>KP</b> (Front of back	□1 □2 □3 □4 □5 □6 □7 □ <u>8</u> □9 □10

Frame colour – one-colour design			
	mple images at: www.proactiv-gmbh.de/farben.php	)	
frame colour: Selection from colour pale	tte		
Frame colour is specified when ordering			
A9000100170-000			
Powder coatings			
White RAL 9016	Brilliant silver	Anthracite RAL 7016	
gloss A9000100170-023	gloss A9000100170-011	gloss A9000100170-001	
matt A9000100170-123 € 40.10		matt A9000100170-101 € 40.10	
Black RAL 9005	Pure orange RAL 2004	Pink magenta RAL 4010	
gloss A9000100170-003	gloss A9000100170-022	gloss A9000100170-037	
☐ matt A9000100170-019 <b>€ 40.10</b>	matt A9000100170-122 € 40.10	☐ matt A9000100170-137 <b>€ 40.10</b>	
Pastel blue RAL 5024	Lemon green	Yellow RAL 1023	
gloss A9000100170-036	gloss A9000100170-005	gloss A9000100170-046	
☐ matt A9000100170-136 <b>€ 40.10</b>	matt A9000100170-105   € 40.10	☐ matt A9000100170-146 <b>€ 40.10</b>	
Red RAL 3001	Lagoon blue	Athletic grey	
gloss A9000100170-047	gloss A9000100170-052	gloss A9000100170-050	
☐ matt A9000100170-147 <b>€ 40.10</b>	☐ matt A9000100170-152 <b>€ 40.10</b>	☐ matt A9000100170-150 <b>€ 40.10</b>	
Muddy grey			
gloss A9000100170-051			
matt A9000100170-151 € 40.10			
"Dormant" powder coatings			
Deep black, silver effect	Sky blue	Marine blue	
gloss A9000100170-007	gloss A9000100170-017	gloss A9000100170-045	
		matt A9000100170-145 <b>€ 40.10</b>	
Electric green	Violet	Fire red	
gloss A9000100170-015	gloss A9000100170-044	gloss A9000100170-018	
matt A9000100170-115 <b>€ 40.10</b>		☐ matt A9000100170-118 <b>€ 40.10</b>	
Frame colour – "liquid coating	" one-colour design		
€ 323.20			
Storm (ice blue)	Coffee	Prairie (rose gold)	
gloss A9000100170-500	gloss A9000100170-520	gloss A9000100170-504	
matt A9000100170-501	matt A9000100170-521	matt A9000100170-505	
Pearl (mother of pearl-white)	Berry	Blue ocean	
gloss A9000100170-524	gloss A9000100170-526	gloss A9000100170-522	
matt A9000100170-525	matt A9000100170-527	matt A9000100170-523	
Emerald (emerald green)	Mint	Chilli	
gloss A9000100170-514	gloss A9000100170-528	gloss A9000100170-516	
matt A9000100170-515	matt A9000100170-529	matt A9000100170-517	

Frame colour – two colour designs			
Note: Frames with two colour designs in the gloss	s level of the design colour.		
Two-colour design comprising one and one design colour (on the front	basic colour (on the back of the frame) of the frame)	€ 248.30	
Please select from the following colours:			
Base colour (on the rear frame)			
White RAL 9016	Brilliant silver	Anthracite RAL 7016	
A9000100170-200	A9000100170-201	A9000100170-202	
Black RAL 9005	Pastel blue RAL 5024	Lemon green	
A9000100170-203	A9000100170-206	A9000100170-207	
Yellow RAL 1023	Lagoon blue	Athletic grey	
A9000100170-208	A9000100170-212	A9000100170-210	
Muddy grey			
A9000100170-211			
Design colour (on the front frame)			
Black RAL 9005	Lemon green	Chilli	
gloss A9000100170-259	gloss A9000100170-250	gloss A9000100170-253	
matt A9000100170-260	matt A9000100170-251	matt A9000100170-254	
Pure orange RAL 2004	Coffee	Mint	
gloss A9000100170-255	gloss A9000100170-278	gloss A9000100170-286	
matt A9000100170-256	matt A9000100170-279	matt A9000100170-287	
		_	
Emerald (emerald green)  gloss A9000100170-274	Storm (ice blue)  gloss A9000100170-264	Prairie (rose gold)  gloss A9000100170-266	
<b>=</b>	<b>=</b>		
matt A9000100170-275	matt A9000100170-265	matt A9000100170-267	
Pearl (mother of pearl-white)	Berry	Blue ocean	
gloss A9000100170-282	gloss A9000100170-284	gloss A9000100170-280	
matt A9000100170-283	matt A9000100170-285	matt A9000100170-281	
Colour - Attachment parts			
· ·	aster fork and bearing block are mounted in black.		
Drive wheel: Aluminium rim, hub and	Caster fork and bearing block		
spokes     Black A9000100171-003	Silver A9000100173-011  Black A9000100173-003		
_			
Attachment parts colour design a Drive wheel: Aluminium rim and	Caster wheel: 5" aluminium rim² (3-spoke		
design inlet <sup>1</sup>	design)		
☐ Pure orange RAL 2004 € 193.10	Pure orange RAL 2004 € <b>44.40</b>		
A9000100171-022  White RAL 9016  € 193.10	White RAL 9016 A9000100174-023  € 44.40		
— A90001001/1-023	☐ Frame colour € 69.50		
A9000100171-999	A9000100174-999  Selection of single colour		
Selection of single colour coating (deviating from	coating (deviating from		
the frame colour)	the frame colour)		
A9000100171-998	A9000100174-998		
	A9000100170-		
7.0000100110 = = = = =			
Special colour requests (frame or attachment parts)			
Frame colour individual procurement Selection from RAL colour palette	Degree of gloss Colour designation  gloss	n RAL number	
☐ A9000100170-100 € <b>383.10</b>	_ `	_	
	☐ matt		
<b>Note:</b> Attachment parts <b>not</b> possible in design colours <sup>1</sup> Only in conjunction with Liteline hub (for drive wheel aluminium rim with 18 or 36 spokes, object).			
<sup>2</sup> Only in conjunction with 5" caster wheel aluminium rim 3-spoke design easy running A9000501200 or good shock absorption A9000501210			

Frames		
Straight front end	Front end abducted	Custom-made seat width dimension
A9050100010-K* Knee angle 100°	A9050100030-K* € 354.20  Knee angle 100° 2.5 cm / side  Abduction starts at: ST 31 cm, size L ST 35 cm, size XL ST 39 cm, size XXL Length of the abduction up to opened dimensions approx. 55 mm	39 - 43 cm  ☐ A9050100060-K001 € 477.30 with frame reinforcement by two cross bar connections
Caster wheel bearing block		
Base plate for bearing block welded  A9050500000  X (see sketch) for frame size Size L: 63 mm Size XL: 74 mm Size XXL: 80 mm		
Push handles		
Aluminium push handles fixed in back tube  A9050401050 from RH 23 cm	Safety push handles with continuous height adjustment  ☐ A9050401060 € 79.80  Mount in the back tube from RH 30 cm with belt cover from RH 43 cm with back shell Starting at a back height of 35 cm for back tube with lordosis support	Safety push handles back-positioned  Length 45 cm A9050401075-K001 € 79.80  Length 55 cm A9050401075-K002  Continuous height adjustable push handle holder back-positioned Up to a SB of 42 cm or a body weight of 95 kg

Safety push handles aluminium back- positioned	Central safety push handle aluminium Foldable handle area	Central push handle for brake handle folding gripping area
with side handle offset 145 mm  A9050401080-K* € 151.50 continuous height adjustment Safety push handle holder mounted on the back cross bar Length: 55 cm Up to seat width of 38 cm or body weight of 60 kg	A9050401086-K € 174.70  Height-adjustable and foldable in the handle area via toothed joint, holder welded on the middle on the back cross bar.  Up to seat width of 38 cm or body weight of 50 kg  Not in combination with headrest fixture guard Note: Not suitable for carrying the wheelchair to do this, grasp the back cross bar.	A9050401070-K € 215.20  Closed, with continuous height adjustment, with foam rubber handle cover Up to seat width of 38 cm or body weight of 50 kg  Not compatible with headrest fixture Only in conjunction with parking knee lever brake for accompanying person or drum brake.
Push handle bar aluminium, closed, foldable via toothed joint		
A9050401069-K € <b>440.30</b> continuous height adjustment push handles shifted to the back Up to seat width of 38 cm or body weight of 60 kg		
41		
Backrest		
Backrest fixed	Folding backrest	Back tube with lumbar curvature
A9047400020 Aluminium side parts bolted Back angle 90° to the ground Backrest cannot be folded	A9000400024 € 283.20 7-way angle adjustment, With integrated plastic coated aluminium side sections	☐ A9000400005-K € 105.80 ☐ 1 cm ☐ 2 cm ☐ 3 cm
Back equipment		
Adaptable back with back padding  A9000802010-K Cover: Black, breathable, open surface Equipment with back cross bar	Equipment without back upholstery and back padding or back system  ☐ A9000802011 € - 53.00  Equipment with back cross bar	

Other back systems, such as ergonomic back shell etc. see separate order sheet: "PRO ACTIV seat and back systems"



You will find our PRO ACTIV transport restraint systems on our separate "Transport restraint systems" order sheet



	ISO 7176-19		
Seat upholstery			
Body Contour	Aluminium seat plate	Equipment without seat upholstery	
A9000801025-K	A9000801210-K € 270.70  Assembly between the frame tubes on bolted welded seat plate holders  Colour: Anthracite matt (Where not specified under colour selection)	A9000801050	
Seat cushion			
58	X = Durchhang  Radius  *  SB		
Seat cushion in rectangular contour Inlet: Standard	Seat cushion with radius contour Inlet: Standard	Seat cushion height:	
☐ A9000805180-K* <b>€ 106.60</b>	☐ A9000800300-K* € <b>148.00</b>	☐ 4 cm ☐ 6 cm	
Seat cushion in rectangular contour Inlet: Anti-Decubitus	Seat cushion with radius contour Inlet: Anti-Decubitus	Seat cushion height:  4 cm	
□ up to 30x30 cm A9000805204-K* € <b>276.20</b>	□ up to 30x30 cm A9000800311-K* € <b>326.50</b>	☐ 6 cm	
>30x30 up to 50x50 cm A9000805200-K* € <b>401.90</b>	>30x30 up to 50x50 cm € 443.70 A9000800310-K*		
Cover:			
☐ Black, breathable, open surface ☐ Black, breathable, closed surface			
If not specified, the cover fabric "black, breatha	ble, open surface" is delivered.		
☐ Seat cushion is existing			
Brand/type			
Cushion heightcm			
You can also find the seat cushions on our separate "PRO ACTIV Seat and Back Systems" order sheet			
Clothing guard			
Aluminium clothing guard removable of Adjustable following wheel arch Only in combination with folding backrest	ria lock function		
in anthracite matt	in frame colour (basic colour with two-colour	in design colour (only possible with frame	
☐ A9000403210-K <b>€ 224.90</b>	design)	colour in two-colour design)	
	☐ A9000403211-K <b>€ 287.60</b>	☐ A9000403212-K <b>€ 319.00</b>	

## Carbon clothing guard removable via lock function A9000400012-K € 521.20 Adjustable following wheel arch Only in combination with folding backrest **Armrests** Armrest, height adjustable, integrated in the clothing guard Including aluminium clothing guard with arm padding 25 cm long Removable via lock function Only in combination with folding backrest in anthracite matt in design colour (only with frame colour in In frame colour (basic colour with two-colour design) two-colour design) A9000400008-K € 526.70 ☐ A9000400010-K A9000400009-K € 575.00 € 599.20 Armrest, height adjustable, integrated Arm padding 25 cm length Armrest can be swung to the side, in the clothing guard mounted on clothing guard removable ☐ A9000403141-K A9000400018-K € 797.00 A9000403151 € 331.50 Upper arm padding edge depending on the Including carbon clothing guard with arm padding 25 cm long with arm padding 25 cm long Positioning: upper arm padding edge approx. clothing guard setting mounted approx. 20 cm to 24 cm above the seat tube. 25 to 31 cm above the seat tube Removable via lock function Only in combination with folding backrest Only in combination with clothing guard adjustable in 1.5 cm increments Not in combination with back-positioned safety push handles Axle plate Standard equipment with 12 mm sockets/axle. Further axle plate on request. Standard axle plate Long axle plate Removable wheelbase extension Speedy 4teen A9016201000 A9016201020 € 217.00 Rear seat height: A9016102001 € 537.50 Rear seat height: size L (22") approx. 33.5 - 37.5 cm size L (22") approx. 35.5 - 41.5 cm wheel position displacement approx. 14 cm size XL (24") approx. 36 - 40 cm size XL (24") approx. 38 - 44 cm 4°/6° camber integrated, adjustable track size XXL (24") approx. 39 - 43 cm size XXL (24") approx. 41 - 47 cm Wheel camber \*Total width with tight-mounted handrim 1° drive wheel camber 4° drive wheel camber 6° drive wheel camber A9016202010 A9016202030 A9016202040 Total width = approx. SB + 20 cm\* $\overline{\text{Tot}}$ al width = approx. SB + 26 cm\* Total width = approx. SB + 30 cm\*

8° drive wheel camber		
☐ A9016202050 € 71.20  Total width = approx. SB + 33 cm*  Only possible up to a body weight of 50 kg		
E-adaptations		
Preparation for "e-motion" mounting	Preparation for "e-fix" mounting	
☐ A9016201200* € <b>465.00</b>	☐ A9016201210* <b>€ 465.00</b>	Wheelchair delivery to
Equipment: e-motion torque support, 1/2" axle and socket length 50.8 mm (2") PRO ACTIV and Alber recommend antitipping supports are installed in pairs. Please choose "Adaptations" under the selection.	Equipment: 1/2" axle, socket length 50.8 mm (2") and e-fix torque support.  PRO ACTIV and Alber recommend antitipping supports are installed in pairs. Please choose "Adaptations" under the selection.  Please order Alber anti-tipping supports and corresponding components direct from Alber.	Alber GmbH (Please also enter on p.1 under "Shipping address, other"!)  Specialist dealer
Brake system		
Brake system push to lock Standard brake handle	Brake system push to lock Long brake lever	Brake system push to lock Low brake handle
A9000701010-001	A9000701010-002	A9000701010-003
RACTIV		PR ACTIV
Brake lever at 20°	Brake system push to lock	Brake system push to lock
A9000700002 Only in conjunction with knee lever brake	Brake lever with M8 adapter and plastic ball	Brake handle to flip-down
system, standard brake lever, long or low	☐ A9000706001 € <b>154.70</b> Only in conjunction with knee lever brake system, standard or long brake lever	☐ A9000706008 € <b>146.70</b> Length: 9 cm
	Brake lever: ☐ Standard ☐ Long	
		R ACTV
Knee lever brake with one-hand operation	Parking knee lever brake for accompanying person	Knee lever brake with lock
A9000707020-K € <b>362.80</b>	A9000701020 € <b>429.10</b>	Brake lever, short
via Bowden cable Operation:	Push handle operation via Bowden cable.	Long brake lever A9000700215 Locking block for brake lever  € 146.70
Left		Prevents braking during pushing by accompanying persons Not possible in combination with knee lever brake with one-hand operation

## **Drum brake** A9000702010-K\* € 438.30 Operating from the push handle Total wheelchair width (see selection "Wheel camber") + 3cm Depending on the seat height, the long wheel plate is mounted in order to protect the drum brake anchors. Please note: - Only in combination with drive wheel aluminium 36-spoke rim wheel - Not in combination with one-hand drive, e-fix or e-motion **Footrest** Continuous footrest Footrest folding up to one side Footbar folds up to the rear with spring locking mechanism A9016601010-K\* € 160.80 A9016601300-K\* with tubular resting bracket € 265.70 A9016602005-K\* with continuous tubular resting bracket, height adjustable +/- 3 cm: height adjustable +/- 3 cm, with continuous tubular resting bracket Size L / XL from USL 26 cm cannot be removed For size L / XL from USL 31 cm Size XXL from USL 29 cm For size L / XL from USL 25 cm For size XXL from USL 35 cm. For equipment of the footrest with "Rubber For size XXL from USL 28 cm For equipment of the footrest with "Rubber coated footplate support", please select under can also be pivoted outwards: coated footplate support", please select under "Footrest accessories" For size L / XL from USL 29 cm "Footrest accessories" For size XXL from USL 32 cm For equipment of the footrest with "Rubber coated footplate support", please select under "Footrest accessories" Footrest folding back to the rear Footrest folding back to the rear for **Divided footrest** USL < 39 cm and from SB 33 cm A9016602010-K\* € 284.70 A9016603200-K € 311.40 A9000600007-K € 325.90 with continuous tubular resting bracket and with rubber coated footplate, locking via 20 mm operating lever height adjustable +/- 3cm, angle adjustment, Foot bracket joint clamped on the frame. can be pivoted outwards and folded up to the Please note: with continuous tubular resting bracket and Size L / XL from USL 39 cm side. 20 mm operating lever Size XXL from USL 42 cm including frame reinforcement For equipment of the footrest with "Rubber with V-shape from SB 33 cm coated footplate support", please select under Please note: Not possible with V-shape. Size L / XL from USL 31 cm "Footrest accessories" Size XXL from USL 34 cm For equipment of the footrest with "Rubber Not in combination with therapy coated footplate support", please select under cannot be removed "Footrest accessories"

"Swing away" footrest	Footrest, positioned on the upper	
	frame	
A9016604100-K € <b>374.20</b>	A9041606010-K	
with rubber coated footplate, centrally divided, can be swivelled to the side, removable,	height-adjustable From USL 20 to 25 cm possible.	
can be folded up, height-adjustable, angle-adjustable	Rubber coated footplate support required,	
including frame reinforcement	please select this under "Footrest accessories"	
Please note: Possible with G-shape size L / XL / XXL	accessories	
and abducted shape size XXL,		
Not possible with V-shape.	1.00	
Footrest accessories		
Rubber coated footplate, 14 cm deep	Rubber coated footplate, 18 cm deep	Footplate side stop
_		☐ A9000610100 € <b>55.20</b>
☐ A9000610000-K <b>€ 116.40</b> bolted, angle-adjustable	☐ A9000610005-K <b>€ 129.50</b> bolted, angle-adjustable	A9000610100 € <b>55.20</b>   adjustable
bonou, angle adjustable	Solica, aligio adjustasio	Please note:
		only in combination with rubber coated footplate!
		I. N
		2
PRO ACTIV		
Deflector rollers mounted on the footplate		
☐ A9000600006 € <b>108.60</b>		
only in combination with rubber coated footplate		
200		
Adaptations		
Anti-tipping support	Universal adapter prepared for anti-	Transit wheels
☐ right side A9000300100-K001 € <b>156.40</b>	tipping support with lifting function from Alber (e-fix, e-motion)	☐ A9000301100 <b>€ 304.80</b>
□ loft side	☐ A9016300105 <b>€ 274.40</b>	with universal adapter, removable not in combination with anti-tipping support
☐ Helt side A9000300100-K002 € <b>156.40</b>	Supplied without anti-tipping support and anti-	not in combination with anti-tipping support
with tension spring and universal adapter pivotable	tipping support mount. On the customer side, please order the anti-	
for optimum pivoting behaviour, the	tipping support by Alber	
seat slope should be >3 cm		
8		
		6

Tilting clamp	Outdoor wheel attachment with	
right side	steering fork	
A9000302100-001 € <b>129.50</b>	☐ A9000900100 € <b>782.00</b>	
☐ left side € 129.50	Equipped with straight-running lock	
A9000302100-002 with universal adapter and Quick pin	can be removed from the wheelchair via quick release lever	
not in combination with anti-tipping support, right side or left side	with swivelling pneumatic tyre 12.1/2 x 2.1/4" caster wheel	
right side of left side	can be removed from the support tube via quick-release axle	
	for maximum ground pressure at the	
	steering attachment of 30 kg	
	AHD .	
Transport restraint connection on the rear frame via frame insert with belt	Bearing block intermediate plate	
eye	with belt eye for mounting the front retractor  Colour: black	
☐ A9000900020 € <b>353.50</b>	△ A9000900008-001 € <b>168.10</b>	
for mounting a lap belt and the rear retractor.  Lap belt and buckle (A9000900001 / A9000900007), please select separately if	Colour: Silver A9000900008-002 € 168.10	
required.	Please note:	
	The wheel track guide increases by 12 mm per side.	
0	<b>1</b>	
Headrest with segment padding	Headrest fixture	
☐ A9000900004 € <b>384.30</b>	pipe dimensions support tube ø 25 mm € 258.60	
3-part and support tube ø 25 mm	A9000900005-K001	
	For mounting the headrest segment padding Please select separately (A9000900004).	
	Reinforced version with double cross-tube.  pipe dimensions support	
	tube 15 x 15 mm € <b>207.60</b> A9000400850-001	
	pipe dimensions support	
	12.7 x 12.7 mm € <b>207.60</b>	
	A9000400850-002 with square holding fixture for headrests.	
	Assembly on the back cross bar. Reinforced version with double cross-tube.	
	Possible from SB 26 cm.  Not in combination with the central push	
	handle.	
	III.	
You will find our PRO ACTIV transport r	estraint systems	

You will find our PRO ACTIV transport restraint systems on our separate "Transport restraint systems" order sheet



3" caster wheel		
3" Skate wheel (80 mm)		
☐ A9000501110		
4" caster wheel		
4" caster wheel "Standard" solid rubber black	4" Skate wheel (100 mm)	4" safety light-up wheel (100 mm)
A9000501011-004 (82A), puncture-proof	☐ A9000501120	A9000501220 € <b>87.60</b> puncture-proof
0		
4" Frog Legs caster wheel (100 mm)		'
☐ A9000501230 <b>€ 196.50</b>		
with replaceable rubber 6 mm, puncture-proof Colour: Black, silver rim Incl. hair guard spacer (5.3 mm)		
5" caster wheel		
5" caster wheel "Standard" PU black	5" Caster wheel "Standard" PU grey	5" Caster wheel "2 components"
A9000501036-005 (82A), puncture-proof	A9000501031-005 (82A), puncture-proof	☐ A9000501030 <b>€ 52.00</b> puncture-proof
5"safety light-up wheel (125 mm)	5" Aluminium rim 3-spoke design	5" aluminium rim 3-spoke design
☐ A9000501221 € <b>87.60</b>	"easy running"	"Good shock absorption"
puncture-proof	☐ Silver, anodised A9000501200 € <b>160.50</b>	Silver, anodised 49000501210 € 166.30
	black A9000501201  With exchangeable rubber ring 3 mm hard, puncture-proof Incl. hair guard spacer (3 mm)	black A9000501211  with replaceable rubber 6 mm medium hard, puncture-proof Incl. hair guard spacer (3 mm)

5" Frog Legs caster wheel (125 mm)		
☐ A9000501232 <b>€ 196.50</b>		
with replaceable rubber 6 mm, puncture-proof Colour: Black, silver rim Incl. hair guard spacer (5.3 mm)		
6" caster wheel		
6" Caster wheel "Standard" PU grey	6" caster wheel "pneumatic tyre"	6" caster wheel "Flexel System"
A9000501010-006 (82A), puncture-proof	☐ A9000501050 <b>€ 52.90</b> SH front min. 42 cm	☐ A9000501070 <b>€ 52.90</b> puncture-proof
Caster fork		
Caster fork colours, see "Component colours"  Caster fork Standard	Heavy duty caster fork	Suspension fork
A9000500100-K001	For high loads or when using additional electric drives	incl. 5" aluminium rim "good shock absorption"
with screwed axle	☐ A9000510111-K001 <b>€ 49.90</b>	☐ A9000500160-K001 € <b>466.90</b> with screwed axle
☐ A9000500100-K002 € <b>154.80</b> with quick-release axle	with screwed axle	☐ A9000500160-K002 € <b>570.40</b>
	☐ A9000510111-K002 <b>€ 202.40</b> with quick-release axle	with quick-release axle
Caster fork spare wheel Standard	Caster fork spare wheel Heavy Duty	The spare caster fork does not have a caster wheel.
A9000500300-K € 274.40	A9000500301-K € <b>312.50</b>	In case a caster wheel is requested, please put a cross on a second selection in the
Standard caster forks with quick-release axles	Heavy duty caster forks with quick-release axles	category "Caster wheels".
Track distance		
Caster wheel track extension		
☐ A9000500400* <b>€ 54.70</b>	☐ A9000500401* <b>€ 54.70</b>	☐ A9000500410* <b>€ 54.70</b>
10 mm per side	15 mm per side	20 mm per side

## **Drive wheels** Information on further rim types, versions and availabilities under: www.proactiv-gmbh.com Drive wheel, 18 spoke aluminium rim Drive wheel, 36 spoke aluminium rim Drive wheel double rim 36 spokes 24" (ETRTO 540) 24" (ETRTO 540) A9000203122 A9000203000 24" (ETRTO 540) € 145.90 with Liteline hub, spoked radially Up to 120 kg body weight with Liteline hub A9000203100 Not in combination with: (left image) 25" (ETRTO 559) Over 120 kg body weight with aluminium high - Puncture-proof tyres € 145.90 A9000203200 - One-hand drive flange (right image) - Drum brake radially spoked 26" (ETRTO 590) - Adaptive bike € 145.90 A9000203300 only up to a body weight of 70 kg: with aluminium front hub, Sturz radially spoked 10° 1 4° 6 8 Use with high loads Gewicht bis 50 Kg 51 - 60 Kg ~ ~ / V 61 - **7**0 Kg Spinergy running wheel "Spox Sport" Spinergy "Everyday Light Extreme" Spinergy "Everyday Light Extreme" with 12 PBO spokes; rim and hub in with 12 PBO spokes; rim, with 24 PBO spokes; rim, hub and spokes in black black, spokes white hub and spokes in black 24" (ETRTO 540) 24" (ETRTO 540) 24" (ETRTO 540) € 725.00 € 885.00 € 885.00 A9000203550 A9000203554 A9000203552 25" (ETRTO 559) € 725.00 A9000201559 26" (ETRTO 590)





€ 725.00



Handrims				
x = dimension handrim attachment				
General: Cu ☐ x = 11 mm ☐	andrim attachment rve handrim: x = 10 mm x = 18 mm			
Unless otherwise specified, the handrim is mour				
Stainless steel Ø 20 mm  □ 24" handrim for 24" wheel and 25" wheel A9000205010-004  □ 26" handrim for 26" wheel A9000205010-006	Aluminium Ø 19 mm silver anodised  24" handrim for 24" wheel and 25" wheel A9000205019-004	Aluminium Ø 19 mm powder coated in frame colour  (basic colour with two-colour design)  □ = Gloss surface □ = Matt surface  Note: Matt coating is not recommended due to the low grip.  □ 24" handrim for 24" wheel and 25" wheel A9000205020-004  □ 26" handrim for 26" wheel € 63.10  A9000205020-006		
Aluminium Ø 19 mm polished and hard-anodised	Titanium Ø 19 mm	Silicone handrim cover		
24" handrim for 24" wheel and 25" wheel A9000205030-004 € 152.50	24" handrim for 24" wheel and 25" wheel A9000205040-004  26" handrim for	for 24" handrim A9000205100-004  ☐ for 26" handrim A9000205100-006  Surface without structure,		
26" handrim for 26" wheel € <b>152.50</b> A9000205030-006	26" wheel € <b>310.30</b> A9000205040-006	compatible with handrim Ø 19 mm or Ø 20 mm.		

Ultra-Grip "very grippy"	Ergo-Grip	Curve black anodised, ergonomic handrim profile
24" handrim for 24" wheel and 25" wheel A9000205070-004	24" handrim for 24" wheel and 25" wheel A9000205080-004 € 377.90	24" handrim for 24" wheel and 25" wheel € 370.60
26" handrim for 26" wheel € <b>372.10</b> A9000205070-006	26" handrim for 26" wheel € <b>377.90</b> A9000205080-006 Attachment fitting to the rim	H 24 mm A9000205130-004  24" handrim for 24" wheel and 25" wheel € 370.60
		H 31 mm, size L A9000205140-004
		26" handrim for 26" wheel H 31 mm, size L A9000205140-006 € <b>370.60</b>
Curve silver anodised ergonomic handrim profile	Curve powder-coated, ergonomic handrim profile	Curve Grip, with Tetra-Grip coating ergonomic handrim profile
24" handrim for 24" wheel and 25" wheel € <b>375.5</b> 0	1 7/1" bondrim tor	24" handrim for 24" wheel and
H 31 mm, size L A9000205160-004	24" wheel and 25" wheel € <b>432.40</b> H 24 mm	25" wheel € <b>481.40</b> H 24 mm A9000205155-004
	A9000205135-004  24" handrim for 24" wheel and	24" handrim for 24" wheel and 25" wheel € <b>481.40</b>
	25" wheel € <b>432.40</b> H 31 mm, size L A9000205145-004	H 31 mm size L A9000205150-004
	☐ 26" handrim for 26" wheel H 31 mm, size L A9000205145-006	
	Profilhohe H: 24mm oder 31mm	

Quadro with Tetra-Grip coating		Gekko black anodised		Gekko silver anodised
24" handrim for 24" wheel and 25" wheel A9000205170-004	€ 492.90	A9000205175-004	477.30	24" handrim for 24" wheel and 25" wheel A9000205185-004 with a robust and replaceable silicone lip, fully
25" handrim for 25" wheel A9000205170-005	€ 492.90	A9000205175-005	477.30	integrated into the profile Profile height 31 mm
26" handrim for 26" wheel A9000205170-006	€ 492.90	26" handrim for 26" wheel A9000205175-006 with a robust and replaceable silicondintegrated into the profile Profile height 31 mm	<b>477.30</b> e lip, fully	
Gekko S black anodised		Equipment without handrims		
24" handrim for 24" wheel and 25" wheel A9000205195-004 with a robust and replaceable silintegrated into the profile Profile height 24 mm	€ 477.30 licone lip, fully	A9000205990		
Spoke guard				
Finger- and spoke guard "transparent"				
for 24" wheel A9000206300-004	€ 191.50			
for 26" wheel A9000206300-006	€ 191.50			
0				

Tyres			
Schwalbe "RightRun"	Schwalbe "RightRun"	Schwalbe "DownTown"	
High-pressure tyre  ☐ 24x1" (540-25)	High-pressure tyre  24x1" (540-25)	Profiled tyres  24x1" (540-25)	
A9000204001-004 Colour: black	A9000204000-004	A9000204010-004 7.5 bar	
7.5 bar	25x1" (559-23) A9000204000-005	7.0 001	
	26x1" (590-25)		
	A9000204000-006 Colour: Grey, black wall 7.5 bar		
750	7.5 Dai		
8:5			
	Silvy Rath Contact	Stoy full darks Charle	
Schwalbe "MarathonPlus Evolution" with "smart guard" puncture protection	Schwalbe "MarathonPlus" with "smart guard" puncture	Schwalbe "One"	
24x1" (540-25) € 45.50	protection	☐ 24x1" (540-25) A9000204123-004 € <b>86.00</b>	
A9000204030-014	☐ 24x1" (540-25) A9000204030-004 € <b>45.50</b>	Colour: black 9 bar	
☐ 25x1" (559-25) A9000204030-015	Colour: Grey, black wall 10 bar		
☐ 26x1" (590-25) A9000204030-016 € <b>45.50</b>			
Colour: black 10 bar			
Puncture-proof tyre"solid rubber	s by Saff Belle Stock		
tyres"			
☐ 24x1" (540-25) A9000204201-004 € 113.40			
Colour: black Not in combination with the 18 spoke drive			
wheel, Spinergy and one-hand drive			
Accessories			
24" MTB spare wheel set			
with double rim (ETRTO 507), aluminium front hub, quick-release axle and stainless steel handrim Mountain bike tyres, selectively:			
☐ A9000203410 <b>€ 650.40</b>	☐ A9000203413 <b>€ 650.40</b>	NOTE: We charge a surcharge for the use of drum brakes	
24x1.75" Schwalbe "Marathon Plus" Brake setting compatible with 24x1" wheel	24x2.1" Schwalbe "SMART SAM Sport" Brake setting not compatible with 24x1" wheel	☐ A9000200004 € <b>210.60</b>	

Through axle with assistance, Large push button	Lockable drive wheel axle clip "Tetra Clip"	Hand air compressor with pressure gauge
☐ A9000200096 <b>€ 97.80</b>	☐ A9000206400 € <b>153.90</b>	☐ A9000901100 <b>€ 98.30</b>
Interlock dimension: 122 / 110 mm Axle diameter: 12 mm Not in conjunction with lockable drive wheel axle clip "Tetra Clip", Not in combination with one-hand drive	Not for Spinergy drive wheels, one-hand drive, drum brake or Liteline hub.	up to 14 bar
Length-adjustable safety belt with buckle	Adjustable safety belt with hook and fastener	Crutch holder with nylon cup
☐ A9000902100 <b>€ 74.60</b>	☐ A9000902110 € <b>59.60</b>	☐ A9000902310 € <b>127.00</b> flexible
SIGMA lighting set	Transport bag for drive wheels	Accessory bag
☐ A9000903270	for 24" wheel A9000903530-004 Ø 76 cm x 2 cm  € 71.90	☐ A9000903600 € <b>70.30</b> 17 cm x 13cm x 5 cm
incl. Micro USB charging cable. Lighting set compliant with road traffic regulations	for 26" wheel A9000903530-006 Ø 83 cm x 2 cm  € 71.90	

Further accessories, e.g., adaptive bikes, steering attachments, etc. see separate order sheet or www.proactiv-gmbh.com

Notes and remarks: